



Figure similar

SIPLUS S7-1200 CPU 1214C AC/DC/relay based on 6ES7214-1BG40-0XB0 with conformal coating, -40...+60 °C, start up -25 °C, compact CPU, AC/DC/relay, onboard I/O: 14 DI 24 V DC; 10 DQ relay 2 A; 2 AI 0-10 V DC, power supply: AC 85-264 V AC @ 47-63 Hz, program/data memory 100 KB


| General information                                      |  |
|--|--|
| Product type designation                                 | CPU 1214C AC/DC/relay                  |
| Firmware version   | V4.1                                   |
| based on   | <a href="#">6ES7214-1BG40-0XB0</a>     |
| Engineering with   |  |
| • STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275                |
| Supply voltage   |  |
| Rated value (AC)   |  |
| • 120 V AC   | Yes                                    |
| • 230 V AC   | Yes                                    |
| permissible range, lower limit (AC)                      | 85 V                                   |
| permissible range, upper limit (AC)                      | 264 V                                  |
| Line frequency   |  |
| • permissible range, lower limit                         | 47 Hz                                  |
| • permissible range, upper limit                         | 63 Hz                                  |
| Input current  |  |
| Current consumption (rated value)                        | 100 mA at 120 V AC; 50 mA at 240 V AC  |
| Current consumption, max.                                | 300 mA at 120 V AC; 150 mA at 240 V AC |
| Inrush current, max.                                     | 20 A; at 264 V                         |
| Output current   |  |
| for backplane bus (5 V DC), max.                         | 1 600 mA; Max. 5 V DC for SM and CM    |
| Encoder supply   |  |
| 24 V encoder supply                                      |  |
| • 24 V   | 20.4 to 28.8V                          |
| Power loss   |  |
| Power loss, typ.   | 14 W                                   |
| Memory   |  |
| Work memory  |  |
| • integrated   | 100 kbyte                              |
| Load memory  |  |
| • integrated   | 4 Mbyte                                |
| • Plug-in (SIMATIC Memory Card), max.                    | with SIMATIC memory card               |
| Backup   |  |
| • present  | Yes; maintenance-free                  |
| • without battery  | Yes                                    |
| CPU processing times                                     |  |
| for bit operations, typ.                                 | 0.085 µs; / instruction                |
| for word operations, typ.                                | 1.7 µs; / instruction                  |
| for floating point arithmetic, typ.                      | 2.3 µs; / instruction                  |

|   |   |
|---|---|
| <b>CPU-blocks</b>   |   |
| Number of blocks (total)                                  | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| <b>OB</b>   |   |
| • Number, max.  | Limited only by RAM for code  |
| <b>Data areas and their retentivity</b>                   |   |
| Retentive data area (incl. timers, counters, flags), max. | 10 kbyte  |
| <b>Flag</b>   |   |
| • Size, max.  | 8 kbyte; Size of bit memory address area  |
| <b>Address area</b>                                       |   |
| <b>Process image</b>                                      |   |
| • Inputs, adjustable                                      | 1 kbyte   |
| • Outputs, adjustable                                     | 1 kbyte   |
| <b>Hardware configuration</b>                             |   |
| Number of modules per system, max.                        | 3 comm. modules, 1 signal board, 8 signal modules   |
| <b>Time of day</b>  |   |
| <b>Clock</b>  |   |
| • Hardware clock (real-time)                              | Yes   |
| • Backup time   | 480 h; Typical  |
| • Deviation per day, max.                                 | 60 s/month at 25 °C   |
| <b>Digital inputs</b>                                     |   |
| Number of digital inputs                                  | 14; Integrated  |
| • of which inputs usable for technological functions      | 6; HSC (High Speed Counting)  |
| Source/sink input   | Yes   |
| <b>Number of simultaneously controllable inputs</b>       |   |
| <b>all mounting positions</b>                             |   |
| — up to 40 °C, max.                                       | 14  |
| <b>Input voltage</b>                                      |   |
| • Rated value (DC)  | 24 V  |
| • for signal "0"  | 5 V DC at 1 mA  |
| • for signal "1"  | 15 V DC at 2.5 mA   |
| <b>Input delay (for rated value of input voltage)</b>     |   |
| <b>for standard inputs</b>                                |   |
| — parameterizable   | 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four  |
| — at "0" to "1", min.                                     | 0.2 ms  |
| — at "0" to "1", max.                                     | 12.8 ms   |
| <b>for interrupt inputs</b>                               |   |
| — parameterizable   | Yes   |
| <b>for technological functions</b>                        |   |
| — parameterizable   | Yes; Single phase : 3 at 100 kHz & 3 at 30 kHz, differential: 3 at 80 kHz & 3 at 30 kHz   |
| <b>Cable length</b>                                       |   |
| • shielded, max.  | 500 m; 50 m for technological functions   |
| • unshielded, max.  | 300 m; for technological functions: No  |
| <b>Digital outputs</b>                                    |   |
| Number of digital outputs                                 | 10; Relays  |
| Short-circuit protection                                  | Yes   |
| <b>Switching capacity of the outputs</b>                  |   |
| • with resistive load, max.                               | 2 A   |
| • on lamp load, max.                                      | 30 W with DC, 200 W with AC   |
| <b>Output delay with resistive load</b>                   |   |
| • "0" to "1", max.  | 10 ms; max.   |
| • "1" to "0", max.  | 10 ms; max.   |
| <b>Switching frequency</b>                                |   |
| • of the pulse outputs, with resistive load, max.         | 1 Hz  |
| <b>Relay outputs</b>                                      |   |
| • Number of relay outputs                                 | 10  |
| • Number of operating cycles, max.                        | mechanically 10 million, at rated load voltage 100 000  |
| <b>Cable length</b>                                       |   |

|  |   |
|--|---|
| • shielded, max.                                       | 500 m   |
| • unshielded, max.                                     | 150 m   |
| <b>Analog inputs</b>                                   |   |
| Number of analog inputs                                | 2   |
| Input ranges   |   |
| • Voltage  | Yes   |
| Input ranges (rated values), voltages                  |   |
| • 0 to +10 V   | Yes   |
| — Input resistance (0 to 10 V)                         | ≥100k ohms  |
| Cable length   |   |
| • shielded, max.                                       | 100 m; twisted and shielded                           |
| <b>Analog outputs</b>                                  |   |
| Number of analog outputs                               | 0   |
| <b>Analog value generation for the inputs</b>          |   |
| Integration and conversion time/resolution per channel |   |
| • Resolution with overrange (bit including sign), max. | 10 bit  |
| • Integration time, parameterizable                    | Yes   |
| • Conversion time (per channel)                        | 625 µs  |
| <b>Encoder</b>   |   |
| Connectable encoders                                   |   |
| • 2-wire sensor  | Yes   |
| <b>1. Interface</b>                                    |   |
| Interface type   | PROFINET  |
| Isolated   | Yes   |
| automatic detection of transmission rate               | Yes   |
| Autonegotiation  | Yes   |
| Autocrossing   | Yes   |
| Interface types  |   |
| • RJ 45 (Ethernet)                                     | Yes   |
| Protocols  |   |
| • PROFINET IO Controller                               | Yes   |
| • PROFINET IO Device                                   | Yes; Also simultaneously with IO-Device functionality |
| PROFINET IO Controller                                 |   |
| • Transmission rate, max.                              | 100 Mbit/s  |
| Services   |   |
| — Number of connectable IO Devices, max.               | 16  |
| PROFINET IO Device                                     |   |
| Services   |   |
| — Shared device  | Yes   |
| — Number of IO Controllers with shared device, max.    | 2   |
| <b>Protocols</b>                                       |   |
| Supports protocol for PROFINET IO                      | Yes   |
| PROFIsafe  | No  |
| PROFIBUS   | Yes; CM 1243-5 required                               |
| AS-Interface   | Yes   |
| Protocols (Ethernet)                                   |   |
| • TCP/IP   | Yes   |
| Open IE communication                                  |   |
| • TCP/IP   | Yes   |
| • ISO-on-TCP (RFC1006)                                 | Yes   |
| • UDP  | Yes   |
| Web server   |   |
| • supported  | Yes   |
| • User-defined websites                                | Yes   |
| Further protocols                                      |   |
| • MODBUS   | Yes   |
| <b>communication functions / header</b>                |   |
| S7 communication                                       |   |
| • supported  | Yes   |
| • as server  | Yes   |

|   |   |
|---|---|
| • as client   | Yes   |
| Number of connections   |   |
| • overall   | 16; dynamically   |
| <b>Test commissioning functions</b>   |   |
| Status/control  |   |
| • Status/control variable   | Yes   |
| • Variables   | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters  |
| Forcing   |   |
| • Forcing   | Yes   |
| Diagnostic buffer   |   |
| • present   | Yes   |
| Traces  |   |
| • Number of configurable Traces   | 2; Up to 512 KB of data per trace are possible  |
| <b>Integrated Functions</b>   |   |
| Counter   |   |
| • Number of counters  | 6   |
| • Counting frequency, max.  | 100 kHz   |
| Frequency measurement   | Yes   |
| controlled positioning  | Yes   |
| Number of position-controlled positioning axes, max.  | 8   |
| Number of positioning axes via pulse-direction interface                                      | Up to 4 with SB 1222  |
| PID controller  | Yes   |
| Number of alarm inputs  | 4   |
| <b>Potential separation</b>   |   |
| Potential separation digital inputs   |   |
| • Potential separation digital inputs   | 500V AC for 1 minute  |
| • between the channels, in groups of  | 1   |
| Potential separation digital outputs  |   |
| • Potential separation digital outputs  | Relays  |
| • between the channels  | No  |
| • between the channels, in groups of  | 2   |
| <b>EMC</b>  |   |
| Interference immunity against discharge of static electricity                                 |   |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2         | Yes   |
| — Test voltage at air discharge   | 8 kV  |
| — Test voltage at contact discharge   | 6 kV  |
| Interference immunity to cable-borne interference   |   |
| • Interference immunity on supply lines acc. to IEC 61000-4-4                                 | Yes   |
| • Interference immunity on signal cables acc. to IEC 61000-4-4                                | Yes   |
| Interference immunity against voltage surge   |   |
| • Interference immunity on supply lines acc. to IEC 61000-4-5                                 | Yes   |
| Interference immunity against conducted variable disturbance induced by high-frequency fields |   |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6                | Yes   |
| Emission of radio interference acc. to EN 55 011  |   |
| • Limit class A, for use in industrial areas  | Yes; Group 1  |
| • Limit class B, for use in residential areas   | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011  |
| <b>Degree and class of protection</b>   |   |
| IP degree of protection   | IP20  |
| <b>Ambient conditions</b>   |   |
| Free fall   |   |
| • Fall height, max.   | 0.3 m; five times, in product package   |
| Ambient temperature during operation  |   |
| • min.  | -40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C  |
| • max.  | 60 °C; = Tmax; Tmax > +55 °C number of simultaneously switched-on digital inputs 7, digital outputs 5, analog inputs 2 (no adjacent points) with horizontal mounting position |
| • At cold restart, min.   | -25 °C  |

|   |   |
|---|---|
| Ambient temperature during storage/transportation   |   |
| • min.  | -40 °C  |
| • max.  | 70 °C   |
| Altitude during operation relating to sea level   |   |
| • Installation altitude above sea level, max.   | 2 000 m   |
| • Ambient air temperature-barometric pressure-altitude  | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); above 2 000 m max. 132 V AC |
| Relative humidity   |   |
| • With condensation, tested in accordance with IEC 60068-2-38, max.   | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions)   |
| Vibrations  |   |
| • Vibration resistance during operation acc. to IEC 60068-2-6   | 2 g (m/s²) wall mounting, 1 g (m/s²) DIN rail   |
| • Operation, tested according to IEC 60068-2-6  | Yes   |
| Shock testing   |   |
| • tested according to IEC 60068-2-27  | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms   |
| Resistance  |   |
| Coolants and lubricants   |   |
| — Resistant to commercially available coolants and lubricants   | Yes; Incl. diesel and oil droplets in the air   |
| Use in stationary industrial systems  |   |
| — to biologically active substances according to EN 60721-3-3   | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request  |
| — to chemically active substances according to EN 60721-3-3   | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-3   | Yes; Class 3S4 incl. sand, dust, *  |
| Use on ships/at sea   |   |
| — to biologically active substances according to EN 60721-3-6   | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request   |
| — to chemically active substances according to EN 60721-3-6   | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-6   | Yes; Class 6S3 incl. sand, dust; *  |
| Usage in industrial process technology  |   |
| — Against chemically active substances acc. to EN 60654-4   | Yes; Class 3 (excluding trichlorethylene)   |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04                            | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)   |
| Remark  |   |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04             | * The supplied plug covers must remain in place over the unused interfaces during operation!  |
| Conformal coating   |   |
| • Coatings for printed circuit board assemblies acc. to EN 61086  | Yes; Class 2 for high reliability   |
| • Protection against fouling acc. to EN 60664-3   | Yes; Type 1 protection  |
| • Military testing according to MIL-I-46058C, Amendment 7   | Yes; Discoloration of coating possible during service life  |
| • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, Class A   |
| configuration / header  |   |
| configuration / programming / header  |   |
| Programming language  |   |
| — LAD   | Yes   |
| — FBD   | Yes   |
| — SCL   | Yes   |
| programming / cycle time monitoring / header  |   |
| • adjustable  | Yes   |
| Dimensions  |   |
| Width   | 110 mm  |
| Height  | 100 mm  |
| Depth   | 75 mm   |

| Weights         |   |
|-----------------|---|
| Weight, approx. | 455 g   |
| last modified:  | 5/29/2024  |